

# SC9133-RTL

## Counting Network Camera

### Preliminary Technical Specifications

Model	SC9133-RTL	White LED	Yes
<b>System Information</b>		IR LED	Yes
CPU	Multimedia SoC (System-on-Chip)	Power Input	IEEE 802.3af PoE DC 12V
<b>Camera Features</b>		Power Consumption	PoE: Max. 12.5W DC: Max. 13.3W
Image Sensor	1/3" Progressive CMOS	Dimensions	140 (D) x 76 (W) x 42 (H) mm
Maximum Frame Rate	1792x1792 @ 30 fps 896x896 @ 30fps 448x448 @ 30fps	Weight	Max. 600 g
On-board Storage	MicroSD/SDHC/SDXC card slot	Casing	Metal, IP66, IK10
<b>Video</b>		Safety Certifications	CE, LVD, FCC
Compression	H.265, H.264, MJPEG	Operating Temperature	PoE/DC: Starting temperature: -30°C ~ 60°C Working temperature: -30°C ~ 60°C
Maximum Streams	Up to 3 simultaneous streams	Storage Temperature	-40°C ~ 75°C
Report Format	JSON/XML/CSV	Warranty	36 months
<b>Network</b>		<b>Installation</b>	
Users	Users Live viewing for up to 10 clients	Installation Height	190 ~ 240 cm
Protocols	IPv4, IPv6, TCP/IP, HTTP, HTTPS, UPnP, RTSP/ RTP/RTCP, IGMP, SMTP, FTP, DHCP, NTP, DNS, DDNS, PPPoE, CoS, QoS, SNMP, 802.1X, UDP, ICMP, ARP, SSL, TLS, IBIS	<b>Accessories</b>	
Interface	10Base-T/100 BaseTX Ethernet (M12, Female, 4pin, D-coded)	Included	Quick installation guide, flat mounting bracket with ears, screw pack
<b>General</b>		Optional	Tilt mounting bracket
Connectors	M12 4pin D-coded for Network/PoE x1 M12 12pin for DC power/ 2x RS485 / 2x DI (max. 60V) / 2x DO x1 Memory card slot x1		
LED Indicator	System power and status indicator		